

# ANNUAL REPORT

2015 | 2016

## What's on our website

In addition to the content that appears in this report, the following can be found online:

### Publications

<http://www.agreement.co.za/page/publications>

The following documentation is included under the *Agrément Certification* tab:

### Assessments by Agrément SA

[http://www.agreement.co.za/uploads/cms/documents/Assessment\\_by\\_Agrement\\_South\\_Africax.pdf](http://www.agreement.co.za/uploads/cms/documents/Assessment_by_Agrement_South_Africax.pdf)

### Certification Process

[http://www.agreement.co.za/uploads/cms/documents/Certification\\_process\\_\\_x.PDF](http://www.agreement.co.za/uploads/cms/documents/Certification_process__x.PDF)

### Relationship between Agrément SA and SABS

[http://www.agreement.co.za/uploads/cms/documents/ASA\\_&\\_SABSx.pdf](http://www.agreement.co.za/uploads/cms/documents/ASA_&_SABSx.pdf)

### Advantages and Benefits of Agrément Certification

[http://www.agreement.co.za/uploads/cms/documents/Advantages\\_and\\_benefitsx.pdf](http://www.agreement.co.za/uploads/cms/documents/Advantages_and_benefitsx.pdf)

### Building Approval and the National Building Regulations

[http://www.agreement.co.za/uploads/cms/documents/Building\\_approval\\_NBRsx.pdf](http://www.agreement.co.za/uploads/cms/documents/Building_approval_NBRsx.pdf)

### The Performance Concept

[http://www.agreement.co.za/uploads/cms/documents/Performance\\_Conceptx.pdf](http://www.agreement.co.za/uploads/cms/documents/Performance_Conceptx.pdf)

### Recommended Procedure (Tendering process)


[http://www.agreement.co.za/uploads/cms/documents/Recommended\\_procedure\\_for\\_tendersx.pdf](http://www.agreement.co.za/uploads/cms/documents/Recommended_procedure_for_tendersx.pdf)





# CONTENTS

Minister's Foreword	04
Chairperson's Statement	08
Board Members	12
Management Report	14
Technical Committee Meetings	20
World Federation of Technical Assessments Organization	22
Financial Statement	24
Certificates Granted	26
Directory of Active Certificates	50
Directory of Inactive Certificates	56
Technical Agency	60





# MINISTER'S FOREWORD

“Agrément South Africa is an important player within the Department of Public Works family and contributes to Government’s role of improving service delivery to the entire economy by executing its strategic mandate.”







As the Executive authority overseeing the activities of Agrément South Africa I am pleased to report that in the year under review, Agrément South Africa achieved a key milestone of becoming a juristic persona. The bill to create Agrément South Africa as a juristic persona was accented to by his Excellency, Hon. Mr Jacob Zuma, President of the Republic of South Africa on 13 December 2015.

During the year under review the Agrément South Africa Act 11 of 2015 followed the prescribed parliamentary process. The draft bill was submitted to parliament and subsequently referred by the speaker of the national assembly to the portfolio committee for consideration. Agrément South Africa observed the process of the portfolio committee on public works until its approval with amendments and subsequently the consideration of the Bill by the National Council of Provinces until it was passed. Parliament then submitted the Bill to the President of the Republic of South Africa for assent.

#### Benefits of the new legislation

The enactment of the Bill paves the way for Agrément South Africa as a juristic persona and this will eliminate the previous challenge the Department of Public Works had with regard to the funding mechanism applied to the entity. Agrément South Africa will continue as a going concern and its important strategic mandate will remain the same. Agrément South Africa will continue to provide assurance to specifiers and users of the fitness-for-purpose of non-standardised construction related products and systems for which there were no national standards or codes of practice.

#### Status quo

The Department of Public Works is leading the newly formed Transitional Task Team that will oversee the formation of the newly formed public entity. The Transitional task team comprises representatives from

the board and management of Agrément South Africa, the Departments of Public Works and Science and Technology and the CSIR. The Task team will manage the transitional arrangements to ensure Agrément South Africa continues to operate as a going concern.

#### Role of innovative construction technologies

The Department of Public Works as the custodian of public assets in South Africa has the potential to enhance the role of innovative construction technologies in the country. As a developing economy with a huge rural population in dire need of infrastructure development, the Department of Public Works believes some of innovative construction technologies can play a key role in fast tracking much needed infrastructure development in rural areas. In the year under review the Department of Public Work has successfully undertaken pilot projects using innovative construction technologies and is pleased to note that overall the results were satisfactory proving that some of those technologies have the potential to fast track infrastructure development. During the State of the National Address in 2016, his Excellency the President noted the role of science, technology and innovation as part of the nine-point plan to respond to sluggish growth. The President stated: *The Department of Science and Technology will finalise the sovereign innovation fund, a public-private funding partnership aimed at commercialising innovations that are from ideas from the public and the private sectors.* This statement clearly emphasises the important strategic role Agrément South Africa plays in the overall macro-economic development of South Africa.


#### Global role for Agrément South Africa

In the year under review, Agrément South Africa championed the safe introduction of innovative technologies within the country. This is an important initiative as it enables the construction industry to make

the correct selection of innovative technologies. Agrément South Africa's rigorous assessment and certification process facilitates the export of South African innovative products and construction systems to the rest of the global economy. The Agrément South Africa assessment procedure allows for advances in national legislation and in global trends to be incorporated as part and parcel of its technical assessment criteria thus allowing the Agency to keep up with current amendments and changes in the global technical trends.

Agrément South Africa is an important player within the Department of Public Works family and contributes to the entire Government's role of improving service delivery to the entire economy by executing its strategic mandate.

I thank the Board of Agrément South Africa on its oversight role and steering the organisation through the transitional phase. I wish to thank the CEO, Mr Joe Odhiambo for his exemplary leadership of the organisation enabling it achieve its strategic mandate in the financial year under review.



Honourable Mr TW Nxesi (MP)  
Minister of Public Works









## CHAIRPERSON'S STATEMENT

“The year under review saw Agrément South Africa continue to play an important strategic role within the greater technical infrastructure delivery sphere of South Africa.”







The Board of Agrément South Africa continued to exercise its oversight role over the Agency. This ensures the efficient and sustainable management of public funds transferred from the Department of Public Works as well as the fees paid in by applicants in the form of technical assessment and annual fees. This is vital for successful corporate governance of Agrément South Africa.

#### Term of office for the current board

The term of the current Board of Agrément South Africa was extended by the Minister of the Department of Public Works until such time as the new members of the Board take office. The extension of tenure of the current Board was to enable the smooth transition of the Agency to a juristic persona. It is viewed as a critical that the agency continue as a going concern without any disruptions in the execution of its important strategic mandate.

#### Role of technical assessments

The year under review saw Agrément South Africa continue to play an important strategic role within the greater technical infrastructure delivery sphere of South Africa. The assessment of non-standardised construction products entails the scientific assessment of products and construction system performance. The assessment process enables the Board's Technical Committee to ensure that the assessment team has applied its mind prior to approving or dis-approving applications for certification. The successful culmination of assessments on applicant's products or construction systems allows the Board to grant a certificate of fitness for purpose. Certificates have deemed to satisfy status in the National Building Regulations and the Building Standards Act 103 of 1977 (as amended). Thus any Agrément South Africa certificate complies with the Act which promotes uniformly in the law relating to the erections of buildings

and other technical infrastructure. This, therefore, gives credence to the Agrément South Africa certificate as it is issued in terms of an Act of Parliament and thus in terms of the Constitution of the Republic of South Africa. The rigorous assessment process of Agrément South Africa ensures that once a certificate is issued one can use the product or system with confidence as it has undergone rigorous scientific assessment and has been proven fit-for-purpose.

#### Operational structure

The year under review saw Agrément South Africa continue to operate under the auspices of the CSIR. Agrément South Africa has been at the CSIR since its inception in 1969. This year is its 47<sup>th</sup> year of existence and Agency continues to render the very important strategic role of assessing the fitness- for- purpose of construction products and systems. During this period Agrément South Africa has performed in an exemplary manner due in part to the support from the CSIR. This support includes but is not limited to that provided by Shared Services, the Executive Director of the Built Environment, the CSIR Executive, and the access to the intellectual capital within the CSIR as well as access to and use of the CSIR testing grounds and laboratories.


#### Agrément South Africa to continue as a going concern

The reason why Agrément South Africa was created and located at the CSIR in 1969 is partially still valid. It is, therefore, the Board's opinion that Agrément South Africa should continue as a going concern, largely 'as is' which will enable it to continue to enjoy the strategic benefits of being within the sphere of a research institution. The Board took the decision that Agrément South Africa will remain within the CSIR campus in Pretoria, Port Elizabeth, and Stellenbosch. The Board acknowledges and appreciates the support from the Department of Science and Technology and the CSIR

over the past 47 years and is grateful that this support will continue to be provided once the transitional arrangements are completed resulting from the new legal status of Agrément South Africa.

### Technical committee

The technical committee of the Board has the key responsibility to review evaluation reports and draft certificates and if satisfied approve them for certification. The technical committee relies heavily on external technical experts for their independent technical opinions. This is extremely vital for the credibility and independence of the expert opinion. In the 47 years of existence, Agrément South Africa has continued to rely on these experts; who have continued to support the Agency in its execution of its strategic mandate. Some of the experts are from CSIR while others are from other government agencies, universities, research organisations and sister assessment organizations overseas. A technical expert is an individual who has the expert knowledge, experience, training or skill to provide an expert professional opinion on the fitness for purpose of a product or construction system intended for use in the construction of a building or infrastructure within the built environment. Agrément South Africa selects technical experts who are recognised as industry leaders within their profession. This enables their professional technical expert opinions to be accepted and respected within the construction industry. The Board of Agrément South Africa is highly grateful to the technical experts it has continued to rely on over the years for their commitment to excellence.



Mr Pepi Selinga  
Chairperson: Agrément South Africa









#### Mandate

Established by the Minister In 1969 as an independent to bring impartial judgement to of innovative construction products in the interest of the

#### Business purpose

The certification of non-standards construction products and systems as well as assessments as well as

#### Relevance

Annually acknowledge South African construction companies for their contribution to the industry and use of their services are

## AGRÉMENT BOARD MEMBERS



**Mr Pepi Silinga**

Chairperson of the Board

CEO: Coega

#### Qualifications:

- M Eng
- Grad Dip Corporate Governance (IOD UK)
- MBA (EBS)
- Grad Dip Company Direction
- Management Development Programme
- Diploma in Industrial Relations
- BSc Civil Eng





**Mr Denzil Fredericks**  
Managing Director: SHEM Consulting & Training (Pty) Ltd

**Qualifications:**

- Consultant in Occupational Health and safety management
- Accredited OHSAS 18001 Auditor
- Environmental consultant and specialist
- Training Expert in OHSAS management
- Specialist in piping and pressure vessels
- Risk management specialist



**Mr Frank Makomo**  
General Manager: South African Bureau of Standards

**Qualifications:**

- NDip – Construction and Operations Management
- MBA
- Cert – Implementation and Evaluation of Quality Systems
- Cert – Concrete Technology
- Cert – General Health and Safety
- Cert – Quality Systems Auditing



**Mr Hans Ittmann**  
Consultant and Logistics expert: Ittmann Consulting (Pty) Ltd

**Qualifications:**

- BMil (BSc)
- BSc Hons – Operations Research
- MSc – Operations Research
- MBA



**Dr Jeffrey Mahachi**  
Chairperson: Technical Committee  
Executive Director: NHBRC

**Qualifications:**

- BSc – Civil Engineering- Hons
- MSc in Information Technology
- MSc Structural Engineering
- PhD Structural Engineering



**Ms Adelaide Ranape**  
Legal Services Manager: Barloworld Africa (Pty) Ltd

**Qualifications:**

- BPROC
- NDip Corporate Law
- LLM – Commercial Law
- LLM – Tax Law



**Ms Mariana Marneweck**  
Consultant

**Qualifications:**

- BSc – Biochemistry, Microbiology
- BSc – Hons – Biochemistry
- M Phil – Future Studies



**Ms Ntebo Ngcobo**  
Lecturer: Dept. of Civil Engineering  
University of Johannesburg

**Qualifications:**

- NDip – Civil Engineering
- BTech – Civil Engineering
- MBA



# MANAGEMENT REPORT

“...Agrément South Africa successfully certificated innovative weigh-in-motion systems. These systems can measure the weight of trucks in motion thereby saving the logistics companies lots of time...”







The year under review has been challenging yet fruitful. Agrément South Africa achieved the highest number of certificates approved in one financial year. Agrément South Africa strives for excellence in all its operations. The mandate of the organisation was re-affirmed in the passing of the Agrément South Africa Bill no 11 of 2015. This Bill re-affirms Agrément South Africa's role as an important element within the technical approval sphere of activities in the country.

### Technical outputs

In the year under review, Agrément South Africa received a total of 28 certificates application for assessment, out of these applications a total of 22 offers for technical assessments were made to various applicants of who accepted the offers. A record number of 38 certificates were issued after successfully completing technical assessment programs.

### Role of the technical innovation industry

These certificates will enable the certificate holders to utilise their products and construction systems thereby safely bringing innovative products to the public in South Africa. Some of these innovative products have socio-economic benefits such as job-creating potential, enhanced thermal and energy performance amongst other benefits. The approval of Agrément South Africa certificates is done by the Board's technical committee in order to separate the technical assessment from the approval process.

The Technical Committee (TeCo) of Agrément South Africa reviews and ratifies evaluation offers. It also reviews and where deemed appropriate, approves draft certificates. The Committee has to satisfy itself that proper procedures are followed; appropriate expertise and all relevant technical issues were involved and considered. The decisions of the committee are based on consensus opinion among the experts and Board

members serving on the Committee.

The membership of the TeCo comprises a minimum of at least three Board members and a number of independent professional experts. The CEO is an ex-officio member of the committee. The CEO convenes TeCo meetings as and when necessary according to workload and the urgency of matters to be dealt with.

Technical experts are selected according to their field of expertise, relevant to the subject matter under consideration.

### Impact of technical assessment

The impact of technical assessment allows new, improved or old technology utilizing new materials, methods of construction and products to be used in the industry. Examples of innovative products which have been safely introduced in South Africa include the use of un-plasticised polyvinyl chloride water pipes which replaced the mild steel water pipes. Pressed steel roofing tiles, used in many areas as an alternative to concrete roofing tiles. We have recently approved several innovative road pavement systems which offer enhanced performance over traditional road surfacing materials.

### Weigh-in motion

In the year under review, Agrément South Africa successfully certificated innovative weigh-in-motion systems. These systems can measure the weight of trucks in motion thereby saving the logistics companies lots of time as the vehicles do not need to stop in order to be weighed at the weighbridges.

### Security door

In this financial year Agreement South Africa approved access control doors which are used to provide

controlled and secure access in banks, offices, consulting rooms and other similar facilities.

The doors include a variety of revolving mantrap and anti-bandit features. Various functionality aspects of this door were assessed. The performance in use of the doors met the criteria of Agrément South Africa.

The innovative aspects of the door are the locking mechanism that is suitable for use in the event of fire, its ability to accommodate power failures by means of an emergency power supply which may be used to unlock the door.

#### Transitional task team

The transitional task team has representatives from the Departments of Public Works, Science and Technology, the Board and Management of Agrément South Africa and the CSIR. The task team makes decisions regarding transitional arrangements for Agrément South Africa and advises the executive authority accordingly for necessary intervention during the transition period. The task team will provide expert advice on issues pertaining to but not limited to finance, supply chain, audit, human resources, change management, legal, information technology and communications management. The role of the task team is to do everything necessary to ensure the Agency is fully operational as *a going concern* by the agreed date.

#### Benefits of the Agrément South Africa Bill

The Agrément South Africa Bill gives Agrément legal persona. This will reinforce Agrément South Africa's role within the overall technical approvals sphere of activities. The roles and responsibilities are clearly stipulated in the Bill. Agrément South Africa will continue to operate as a going concern. Therefore there will be a seamless transition. To minimise any disruption the Board of Agrément South Africa took the

decision to continue to operate in its current location within the head office in Pretoria and additional offices in Port Elizabeth and Stellenbosch. One of the key benefits to the agency is that it will become more visible as it becomes autonomous from the CSIR. The increased visibility is likely to increase the impact of the organisation thus bring innovative construction technologies to the fore. The Agrément South Africa bill allowed for a transitional period. The Department of Public Works chairs the Transitional Task Team.

#### Extract from the Agrément South Africa Act no. 11 of 2015

*(As introduced in the National Assembly (proposed section 75); explanatory summary of Bill published in Government Gazette No. 38396 of 16 January 2015) (MINISTER OF PUBLIC WORKS)*  
ISBN 978-1-4850-0207-9

#### Bill

To provide for the establishment of Agrément South Africa as a juristic person; to determine its objects, powers and duties; to prescribe the manner in which it is managed and governed; to provide for transitional arrangements; and to provide for matters connected therewith.

BE IT ENACTED by the Parliament of the Republic of South Africa, as follows:—

#### Administrative justice

- 2.(1) Any administrative process conducted or decision taken in terms of this Act must be conducted or taken in accordance with the Promotion of Administrative Justice Act, 2000 (Act No. 3 of 2000), unless otherwise provided for in this Act.
- (2) All notices required in terms of this Act shall be





submitted in writing.

### Agrément South Africa

3. (1) Agrément South Africa, which was established by the Minister and which exists when this Act takes effect continues so to exist and is a juristic person.

(2) The PFMA applies to Agrément South Africa.

### Objects

4. The objects of Agrément South Africa are to—

- (a) provide assurance to specifiers and users of the fitness-for-purpose of non-standardised construction related products or systems;
- (b) support and promote the process of integrated socio-economic development in the Republic as it relates to the construction industry;
- (c) support and promote the introduction and use of certified non-standardised construction related products or systems in the local or international market;
- (d) support policy makers to minimize the risk associated with the use of a non-standardised construction related product or system; and
- (e) be an impartial and internationally acknowledged South African centre for the assessment and confirmation of fitness-for-purpose of non-standardised construction related products or systems.

### Powers and duties

5. (1) In order to achieve its objects, Agrément South Africa may exercise the power to—

- (a) assess and, if satisfied, certify the fitness-for-purpose of a non-standardised construction related product or system;
- (b) issue, amend, suspend, reinstate, withdraw or renew an Agrément Certificate;

- (c) enter into an agreement with a person, entity or organ of state, whose services are required to achieve an object or perform a function of Agrément South Africa or the Board;
- (d) provide services in relation to the objects of Agrément South Africa to a person, entity or organ of state; and
- (e) exercise any other power as may be prescribed or necessary to achieve the objects of Agrément South Africa.

(2) In order to achieve its objects Agrément South Africa has the duty to—

- (a) create appropriate structures to execute its executive and operational functions;
- (b) develop any rules, processes, procedures, criteria or guidelines necessary to achieve the objects of Agrément South Africa and the execution of its duties;
- (c) monitor and evaluate the quality management systems of a certified construction related product or system, in its manufacture, application, installation or erection processes;
- (d) communicate relevant information to stakeholders in respect of the technical, socio-economic and regulatory aspects of a non-standardised construction related product or system certified by Agrément South Africa;
- (e) support and promote the introduction and use of certified non-standardised construction related products or systems in the local or international market;
- (f) establish and maintain international links with peer organizations;
- (g) open and operate a banking account in the name of Agrément South Africa; and
- (h) encourage research and development of non-standardised construction related products or systems.

- (3) Agrément South Africa may-
- (a) acquire or dispose of property or a right in respect thereof, but immovable property may only be acquired or disposed of with the prior written consent of the Minister;
  - (b) invest its funds not immediately required;
  - (c) insure Agrément South Africa against any—
    - (i) loss, damage or risk; or
    - (ii) liability it may incur in the application of this Act;
  - (d) institute or defend legal action;
  - (e) determine, charge and collect fees for any services rendered and product and document produced;
  - (f) charge interest in respect of money due to it from the day after such money becomes due and payable; and
  - (g) grant a person, entity or organ of state an exemption from the payment of any fee, or a portion thereof.

- (4) The powers and duties of Agrément South Africa must be exercised and performed impartially and without undue influence.

### Certification

6. (1) Agrément South Africa must make rules in terms of section 28 to determine the processes, procedures and forms for and relating to the—
- (a) issuing;
  - (b) amendment;
  - (c) suspension;
  - (d) reinstatement;
  - (e) withdrawal; or
  - (f) renewal,
- of an Agrément Certificate.

- (2) Subject to the payment of the required fees, Agrément South Africa must issue a certificate in the prescribed form, if it is satisfied that a

non-standardised construction related product or system is fit-for-purpose.

- (3) An Agrément Certificate is valid for three years from the date of issue thereof, subject to—
- (a) there being no changes to the subject matter for which such certificate is issued;
  - (b) the conditions of certification as stipulated thereon;
  - (c) changes in the law or national standard.

- (4) Agrément South Africa may, by notice to a certificate holder stipulating the reasons therefor and the effective date thereof—
- (a) amend, suspend or withdraw a condition stipulated in the Agrément Certificate or impose a new condition; or
  - (b) amend, suspend or withdraw the Agrément Certificate.

- (5) It is an offence for a person to falsely represent that a construction related product or system is certified by Agrément South Africa, if an Agrément Certificate has not been issued for such product or system or if such certificate has been suspended or withdrawn in terms of subsection (4).


- (6) A person who commits an offence in terms of subsection (5) is liable on conviction to a fine or to imprisonment for a period not exceeding three years.

### Renewal of certificate

7. (1) A certificate holder must, at least three months prior to the expiry of the existing Agrément Certificate, apply to Agrément South Africa for the renewal of such certificate.

- (2) Agrément South Africa may condone the late application for the renewal of the certificate referred to in subsection (1).





(3) An application for renewal referred to in subsection (1) must be in the prescribed form and accompanied by the prescribed fee.

The management and staff of Agrément South Africa would like to express their gratitude for the continued guidance and support from the Minister of Public Works, Mr TW Nxesi, the Deputy Minister Mr. Jeremy Cronin, the Director General Mr Mziwonke Dlabantu, the Board of Agrément South Africa and Technical experts who are the members of the Technical Committee. Your support is highly appreciated, without which Agrément South Africa would not have been able to execute its mandate.



Mr Joe Odhiambo  
CEO: Agrément South Africa





## TECHNICAL COMMITTEE MEETINGS

Certificates approved during the 2015/2016  
Financial Year



# TECHNICAL COMMITTEE MEETINGS

MONTH	ATTENDEES	CERTIFICATES APPROVED BY COMMITTEE
July	Dr Jeffrey Mahachi (Chairperson) Mr Hans Ittmann Ms Ntebo Ngcobo Ms Mariana Marneweck	Abacus Ezee Space Building System Besta Board Building System Boen EcoSolutions Building System Geopanel Formwork for Concrete Construction Geoplast Modulo Foundation System ITAS Access Control Doors Jets Vacuum Sanitation System Kwikspace Building System Modular Fibre Reinforced Concrete Building System Polyform Building System Shouguang Building System Sterling Building System Sutherland Sheen Coating System Sutherland Tex Coating System TCE Water Storage Tanks
December	Mr Hans Ittmann Ms Mariana Marneweck Ms Ntebo Ngcobo	4Everframe Composite Door Frame Abod House Building System Direct Sanitation Application System Ecobond Non-traditional Soil Stabilizer Makoro Water and Liquid Storage Tanks Mikros Dual Stick-on Loop Traffic Monitoring System Permanent Axle Traffic Monitoring System- AUTOPIZO8 Permanent Axle Traffic Monitoring System- PICOTEL8 Permanent Dual Traffic Monitoring System- TELOOP8 Permanent Dual Traffic Monitoring System- TELOOP8-F Permanent Dual Traffic Monitoring System- WYPROS Pro Close Slip-Clutch Garden Bib Tap Pro-phalt Infrared Road Repair System Selcrete Building System TES Stick-on Loop Traffic Monitoring System
March	Dr Jeffrey Mahachi (Chairperson) Mr Hans Ittmann Mr Joe Odhiambo	BravoMax Building System Durafoil DSD Reflective Roof Insulation Foil Everite Siporex AAC Building System I-Wall Building System Tensa Finger RSFD Bridge Deck Joint UL-M 20/10 Thin Bituminous Road Surfacing System

# WFTAO

WORLD FEDERATION OF TECHNICAL ASSESSMENT ORGANIZATION



- 1** Australia  
Australian Building Codes Board (ABCB)
- 2** Brazil  
Instituto de Pesquisas Tecnológicas do Estado de São Paulo S.A. (IPT)
- 3** Canada  
Canadian Construction Materials Centre, NRC (CCMC)
- 4** Czech Republic  
Technical and Test Institute for Construction (TZUS)
- 5** Denmark  
ETA-Danmark (ETA)
- 6** Finland  
VTT Building and Transport (VTT)
- 7** France  
Centre scientifique et technique du bâtiment (CSTB)
- 8** Germany  
Deutsches Institut für Bautechnik (DIBt)
- 9** Hungary  
Non Profit Company for Quality Control and Innovation in Building (ÉMI Kht)
- 10** Ireland  
NSAI Agrément (NSAI)
- 11** Israel  
National Building Research Institute (NBRI)
- 12** Japan  
The Building Center of Japan (BCJ)
- 13** Japan  
The Center for Better Living (CBL)
- 14** New Zealand  
Building Technology Limited/BRANZ (BRANZ)
- 15** Norway  
Norges Byggeforskningsinstitut (NBI)
- 16** Poland  
Instytut Techniki Budowlanej (ITB)
- 17** Portugal  
Laboratório Nacional de Engenharia Civil (LNEC)
- 18** Romania  
Institutul National de Cercetare-Dezvoltare in Constructii si Economia Constructiilor (INCERC)
- 19** Russian Federation  
Science -Technical Centre for Certification in Construction (FCC)
- 20** South Africa  
Agrément South Africa (ASA)
- 21** Spain  
Instituto de Ciencias de la Construcción (IETcc)
- 22** United Kingdom  
British Board of Agrément (BBA)
- 23** United States  
ICC Evaluation Service Inc. (ICC-ES)







# ANNUAL FINANCIAL STATEMENT

Internal Audit Services (IAS) has been requested to provide a certificate to confirm the attached Statement of Revenue and Expenditure for Agrément South Africa for the period 01 April 2015 to 31 March 2016.

IAS confirms that the statement agrees with the balances for the project in the financial records of the CSIR. In addition, IAS has performed the following audit procedures:

- Agreed income received to supporting documentation.
  - Verified on a sample basis, the labour hours per the accounting records to the approved timesheets and the labour rates to the approved charge out rates per the accounting records.
  - Selected a random sample of running expenses and agreed to supporting documentation.
- The results of the above procedures are satisfactory and no exceptions were noted.

In addition IAS performs an annual review of the key financial controls to cover aspects such as authorisation, validity/authenticity of transactions and proper recording. The results of the audit recently completed did not yield any issues of concern.

The statement of income and expenditure reviewed is attached and signed for identification by ourselves.

Regards,

**PONI NGWATO**  
**MANAGER: RISK ASSURANCE AND IT**  
**INTERNAL AUDIT SERVICES**  
**11 AUGUST 2016**





# STATEMENT OF REVENUE AND EXPENDITURE FOR AGRÉMENT SOUTH AFRICA

for the financial year ended 31 March 2016

	2016 R	2015 R
<b>REVENUE</b>	<b>13 868 461</b>	<b>11 650 973</b>
Parliamentary Grant	10 268 368	9 667 544
Department of Public Works Annual Grant	10 247 368	9 667 544
Parliamentary Grant: CSIR	21 000	0
Contract income	3 600 093	1 983 429
Local Private Sector	3 326 926	1 823 233
Local Public Sector	19 000	0
International Sector	254 167	160 196
Other income	14 665	9 512
<b>Total Operating income</b>	<b>13 883 126</b>	<b>11 660 485</b>
<b>Expenditure</b>		
Employees' Remuneration	7 215 711	5 927 633
Depreciation	274 623	516 002
Operating Expenses	6 029 035	5 031 456
<b>Total Operating Expenditure</b>	<b>13 519 369</b>	<b>11 475 091</b>
Finance Income	162 267	181 848
<b>Margin for the year</b>	<b>526 024</b>	<b>367 242</b>

# CERTIFICATES GRANTED

## ABACUS EZEESPACE BUILDING SYSTEM

Abacus EzeeSpace Building System is made up of a standard 6100 mm long x 3050 mm wide x 2850 mm high exoskeleton steel frame. The frame comprises a steel exoskeleton with four corner posts and 1200 mm wide x 2480 mm high x 73 mm thick panels which are slotted between the corner posts.

The foundation and floor slab are conventional and can either be raft or suspended steel floor. Steel must either be hot-dip galvanised in accordance with **SANS 121** or powder coated. The design, erection and approval of the foundation are the responsibility of a registered competent person.

The external wall panels consist of a 60 mm thick Expanded Polystyrene (EPS) core with a density of 15 kg/m<sup>3</sup>. The EPS core is clad with 0.58 mm Chromadek on both sides. The external wall is lined with a 12 mm Superboard on its internal face. The internal wall is constructed using a 40 mm thick EPS core clad with 12 mm Superboards on both sides. Panel joints comprise tongue and groove sections.

The roof structure is constructed from light gauge galvanised steel trusses that are designed and erected in accordance with **SANS 517** and clad with light- or heavy-weight cladding. The roof structure is the responsibility of an approved competent person.

Door frames are made from aluminium or powder coated steel and window frames are made from aluminium. Both window and door frames are factory fitted onto the panels during manufacturing stage.

## BESTA BOARD BUILDING SYSTEM

Besta Board Building System is a single-storey structure that utilizes factory produced Fibrous Magnesium Oxide (MgO) boards and a light-weight steel superstructure that is sub-supported with a hot-dipped galvanised light-gauge steel frame designed and erected in accordance with **SANS 517**. The foundations and roofs are conventional and are the responsibility of an approved competent person.

The steel is hot-rolled and complies with the requirements of **SANS 3575/ISO 3575** or **SANS 4998/ISO 4998**, and has a coating equivalent in corrosion resistance and robustness to galvanizing (Z275).

The external walls are made up of a light-gauge steel frame clad on either side with 12 mm thick MgO boards and the cavity is filled with 100 mm thick (24 kg/m<sup>3</sup>) mineral fibre insulation. Internal walls are made up of a light-gauge steel frame clad on either side with 10 mm thick MgO boards and the cavity is filled with 60 mm thick (24 kg/m<sup>3</sup>) mineral fibre insulation. The steel frame consists of studs spaced at 400 mm centres with bracings. The studs for external walls are 102 mm x 30 mm x 0.8 mm C-sections. The top and bottom rails for external walls are 103 mm x 30 mm x 0.8 mm C-sections. The studs for internal walls are 63 mm x 30 mm x 0.4 mm C-sections. The top and bottom rails for internal walls are 65 mm x 30 mm x 0.4 mm C-sections.

The roof consists of conventional steel or timber trusses with light- and heavy-weight cladding. The ceiling is conventional or 6 mm thick Besta™ board.



## BOEN ECOSOLUTIONS BUILDING SYSTEM

Boen EcoSolutions Building System utilizes conventional concrete foundations and a 100 mm thick surface bed which are the responsibility of an approved competent person.

The exterior wall panels are 2100 mm x 1220 mm x 102 mm thick comprising an 82 mm thick flame-retardant honeycomb paper core ( $62 \text{ kg/m}^3$ ) encapsulated with a 10 mm fibre cement board on either side. The interior wall panels are 2100 mm x 1220 mm x 64 mm thick comprising a 52 mm thick flame-retardant honeycomb paper core ( $62 \text{ kg/m}^3$ ) encapsulated with a 6 mm fibre cement board on either side. Exterior and interior wall panels are plastered and painted with a waterproof coating.

The building structure is made up of a single layer of a lightweight galvanized steel frame with strip footings. The steel studs are manufactured from cold-formed steel that is designed and erected in accordance with the carbon steel requirement of **GB/T700-1988** and high-strength low-alloy structural steel which is designed and erected in accordance to the requirement of **GB/T691-1994**. The frame beams, columns anchor bolts and support systems use Q235B steel. The side flashing edges are connected using self-tapping steel screws.

Roofs are doubled pitched and comprise the same material as that of the wall panels. The roof is supported by the steel structure and is constructed with 2440 mm x 1220 mm x 102 mm thick panels, and covered by a layer of 2.7 mm thick asphalt shingles. The roof structure consists of purlins and H-type steel sections into which the roof panels are slotted. The roof is fitted with PVC gutters and downpipes.

## BRAVOMAX BUILDING SYSTEM

Bravomax Building System is a single-storey structure that utilises factory produced wall panels.

Foundations are conventional concrete rafts with thickened edge beams and thickened floor slabs under internal walls. The design and approval thereof are always the responsibility of a registered competent engineer.

The external and internal wall panels are generally 2400 mm or 3000 mm high x 600 mm or 1200 mm wide with 90 mm thick braced surround steel frames encapsulating a Vermiculite light-weight foam concrete with a density of  $350 \text{ kg/m}^3$  to  $450 \text{ kg/m}^3$ . Walls are finished with 10 mm structural plaster on both sides, resulting in an overall wall thickness of 110 mm.

The frames are manufactured from 90 mm x 30 mm x 10 mm x 0.2 mm thick hot-dip galvanised light gauge steel channels that conform to the requirements of **SANS ISO 4998**, **SANS 121/ISO 1461** and **SANS ISO 3575**.

Roofs are hipped-shaped and are constructed from medium-gauge galvanised steel or timber trusses that are designed and erected in accordance with **SANS 517** and **SANS 10162** respectively, and are always the responsibility of a registered competent engineer.

Doors and window frames (steel, aluminium or Agrément approved) are factory-fitted.

Plumbing and electrical conduits can be pre-fixed or surface mounted onto the composite panels.



## DIRECT SANITATION APPLICATION SYSTEM

Direct Sanitation Application System is a one-litre low flush sanitation system, owner maintained and odourless all-terrain flushing toilet. The sanitation system components should be installed in a top structure/closet with a floor, walls and roof of material adequate for its purpose and the closet should be provided with a door to ensure privacy of occupants in accordance with the National Building Regulations, **SANS 10400-Part Q**.

It is a high-density toilet structure that is installed in areas where sewer networks cannot be constructed. The system, however, makes provision to be changed into a flushable toilet whenever a sewer network is constructed.

A one-litre flush is used to clear the excreta into a 30-litre liquefier tank. The excreta break up in the water and the inflow after each flush causes agitation, which helps in the liquefying of solids.

Water for the Direct Sanitation Application System is stored in a 36-litre tank located behind the toilet wall. Rain, tap or clean river water can be used. One litre of water is used per flush to break down the effluent.

The effluent generated undergoes both aerobic and anaerobic digestion through natural bacteria and protozoa present. When the system operates under these conditions the generation of noxious gasses is limited.

The toilet is designed for a maximum of 7 people per household; any additional usage will require an additional or larger soakaway configuration.

## DURAFOIL DSD REFLECTIVE ROOF INSULATION FOIL

The Durafoil DSD Reflective Roof Insulation Foil is a six layer composite consisting of two layers of aluminium foil laminated to each other with one layer of polyethylene, reinforced with one layer of fibreglass scrim and two layers of graded polyethylene. The spunbond layer is UV-stabilised. The membrane has a weight of  $168 \text{ g/m}^2 \pm 10\%$  and the thickness varies between 0.12 mm to 0.14 mm. It is supplied in rolls of 30 m or 40 m long and 1.25 m wide.

Durafoil DSD Reflective Roof Insulation Foil is suitable for installation in domestic and industrial buildings used in conjunction with timber (pitches equal to or greater than  $10^\circ$ ) or steel roof construction with concrete roof tiles or galvanised sheet steel cladding, provided that fire sprinkles are installed for industrial application. It can be used in all regions of South Africa for all types of occupancy classification (**SANS 10400: Table 1 of regulation A 20 (1)**). When used as stated in the certificate it can:

- reduce air leakage
- reduce ingress to the roof space of wind-driven rain and dust.



### ECOBOND NON-TRADITIONAL SOIL STABILIZER

Ecobond, a non-traditional soil stabilizer, is a modified bitumen emulsion polymer. It is used for stabilizing road base construction materials for both paved and non-paved gravel roads as well as in wearing course for gravel roads.

Ecobond is produced on site through a chemical reaction by mixing bitumen emulsion, synthetic resin, water and a proprietary catalyst. The mixture is added to crushed stone, natural gravels or sand to form a water resistant, elastic and robust layer. It improves the compressive, tensile and shear strength and also the abrasion and water resistance of the particulate materials for road construction. It is insoluble in water and hence does not leach.

The mixing ratios and application rate (mix design) depend on the site specific material and the required road design specifications.

Ecobond is applied at ambient temperature and by use of water tanker trucks. It is applied as a form of bitumen stabilizing material and the standard design methods detailed in SANRAL's manual SAPEM 2013 and SABITA's TG2 are applicable. Alternatively Techneco (Pty) Ltd.'s guideline documents offer application methods.

### EVERITE SIPOREX AAC BUILDING SYSTEM

Everite Hebel Autoclaved Aerated Concrete (AAC) Building System is an ultra-light concrete masonry product that consists of basic materials that are widely available. These include sand, cement, lime, fly ash, gypsum, aluminium powder paste, water and an expansion agent.

The panels are factory manufactured with external walls, 100 mm, 140 mm or 200 mm thick. Walls cast in either of two grades of aerated autoclaved concrete referred to as:

- G4/600- having a density of 580 kg/m<sup>3</sup>
- G5/800- having a density of 725 kg/m<sup>3</sup>

The foundations are conventional concrete strip footings or concrete raft with thickened edge beams. They are always the responsibility of a registered professional competent engineer.

The roof structures are conventional, and constructed from light-gauge galvanised steel trusses must be designed by a professional registered competent engineer and erected under his supervision. The roof structure is clad with light- or heavy-weight cladding. Engineered timber gangnail trusses with a timber wall plate can also be used if required.

All services are conventional and electrical conduits are chased into the wall surface as one would do for conventional brick structures. The grooves are then filled using proprietary filling compound which is then sanded down and plastered over or simply painted depending on finishing requirements. These services must be specified and installed in accordance with good building practice.

### GEOPANEL FORMWORK SYSTEM

GeoPanel Formwork System is a temporary shuttering system for the construction of concrete walls, columns and beams. It consists of a series of various sized panels joined together by the Geoplast fast-lock nylon handle. The formwork system is made of acrylonitrile-butadiene-styrene (ABS) polymer and other additives (pigments, polymer additives, antioxidants, and colourants).

The GeoPanel Formwork System range includes the following products:

- Geopanel: for reinforced cast-in-situ concrete walls and solid reinforced concrete slabs
- Geopanel star: special formwork for reinforced concrete columns in rectangular panels. This formwork is interlockable and adjustable, resulting in different sizes of square and rectangular columns using the same panels
- Geotub: for round reinforced cast-in-situ concrete columns
- Geotub panel: for square and rectangular reinforced cast-in-situ concrete columns, panels in predetermined sizes with chamfered corners

**NB.** Assembly and dismantling of GeoPanel Formwork System is always the responsibility of a registered competent engineer.

### GEOPLAST MODULO FOUNDATION SYSTEM

Geoplast Modulo Foundation System consists of a permanent formwork (Modulo) in recycled polypropylene (PP) that creates a system of pillars and arches supporting the ground floor slab once concrete is poured on them. The foundations are always the responsibility of an approved competent person.

The Modulos are surrounded by reinforced edge and centre beams to support the wall loads and increase stiffness as required by the loading and soil conditions of specific sites. The modulos are available in area dimensions of 500 x 500 mm or 580 x 580 mm or 710 x 710 mm with 18 various heights ranging from 30 mm to 700 mm. The thickness of the concrete topping above, beam sizes and reinforcement are the responsibility of an approved competent person.

Minimodulos formwork with area dimensions of 500 x 500 mm or 580 x 580 mm are also formed with size range of between 30 mm to 90 mm of height.

Mutlimodulo formwork is produced from four or more Modulo moulds connected together to form a single unit formwork of area dimensions of 710 x 710 mm with various heights of between 130 mm to 400 mm.

The foundations are ventilated by creating openings of between 80 to 120 mm Ø using PVC or metallic pipes along the perimeter beams of the foundation in accordance with the design.

The design is in such a way that the slab of the structure is suspended from the ground and a void created beneath is used for ventilating the under-slab surface and housing of services like cables and pipes.



## ITAS ACCESS CONTROL DOORS

ITAS Access Control Doors are security doors that are fabricated in a factory using mainly steel, aluminium and glass. The doors include a variety of revolving, mantrap, bandit and anti-bandit and are:

- ITAS two and four door public mantrap doors
- ITAS revolving doors
- ITAS combo doors
- ITAS small-foot mantrap doors
- ITAS big-foot mantrap doors
- ITAS Anti-bandit electric dead bolt locking exit doors with fire door capabilities
- ITAS Anti-bandit magnetic locking emergency exit doors with fire door capabilities
- ITAS two combo door with adjoining hinged sliding door.

## I-WALL BUILDING SYSTEM

I-Wall Building System is a single-storey structure that utilises factory produced panels that consist of 100 mm thick expanded polystyrene (EPS) for external walls and a 100 mm or 75 mm thick EPS for internal walls. Wire mesh, which acts as plaster key is secured to both sides of the wall panels. Wall panels are then rendered both sides with 25 mm thick spray applied plaster with the resultant overall thicknesses of 150 mm and 125 mm, respectively.

Both external and internal EPS panels are 2400 mm high with 600 mm, 900 mm or 1200 mm widths. The heights of gable wall panels are determined by the pitch of the roof. Wall panels have grooved vertical edges which accommodate column Masonite biscuits projecting either side to slot into the EPS wall panels.

Foundations are concrete rafts comprising 75 mm thick surface beds on damp proof membranes with thickened perimeter edge beams. Surface beds are also thickened under internal walls.

Roof construction is conventional. Trusses can either be timber or light gauge mild steel with light- or heavy-weight cladding.

Door and window frames can be aluminium, timber, precast concrete or Agrément approved.

### JETS VACUUM SANITARY SYSTEM

Jets Vacuum Sanitary System is a vacuum sewage collection and transport system designed for single or multiple flushing of toilets. The system is manufactured by Jets Vacuum AS in Norway and supplied by SA Biotech (Pty) Ltd, based in Benmore, Johannesburg.

The vacuum toilet system uses air, as opposed to water for the transport of sewage. A Jets Vacuumator™ evacuates air from the drain pipes automatically upon activation of the activator button. A valve opens in the toilet, and the difference in air pressure that results causes the sewage to be flushed. Jets Vacuumator™ shreds the sewage whilst pumping it towards a collection tank or a BIOTank. Potable water (1 litre) is automatically fed to the toilet as part of the cycle, ensuring good hygiene with minimum water consumption.

The Jets Vacuumator™ is the main component of the vacuum system. The vacuumator is a viscous monoblock pump fitted with macerators. It extracts the sewage and then shreds it into tiny particles all in one operation. The vacuumator handles air and liquids as well, combining both elements at once. Thus it can be used to produce a vacuum, or for suction and pumping of liquids.

A grey water tank is used in the system where the drains from sinks, showers etc. are connected to the vacuum system. The waste water is fed to the tank via a gravity feed system. The tank is fitted with a drain valve connected to the vacuum system and when full, it empties automatically via the vacuumator.

### KWIKSPACE MODULAR BUILDING SYSTEM

Kwikspace Modular Building System is a single storey structure that utilises factory produced wall and roof panels.

The design and approval of the foundation are always the responsibility of a registered professional competent engineer. Steel must always be hot-dip galvanised in accordance with **SANS 121/ISO 1461**.

The external wall panels are typically 2400 mm x 1160 mm x 40 mm thick with tongue and groove edges consisting of two skins. An outer skin of 0.47 mm galvanised chromadek sheeting encapsulating polyurethane foam with a density of 36 kg/m<sup>3</sup> and a 12 mm inner skin of magnesium oxide board (MgO).

Internal walls are made of the same material as the external walls excluding the MgO board with back to back configuration with no airspace between the wall panels.

Roof panels are made of 40 mm thick expanded polystyrene sandwiched between 0.47 mm chromadek and galvanised inverted box rib (IBR) roof sheet.

The panels are delivered on site with factory-fitted window and door frames (steel, aluminium or Agrément approved) and are purposely made to suite the design of the building system.

Plumbing and electrical conduits can be pre-fixed or surface mounted onto the composite panels.



### MAKORO WATER AND LIQUID STORAGE TANKS

Makoro Water and Liquid Storage Tanks are moulded from polyethylene powder through a rotational moulding process. The production method is well known and is suitable and reliable for manufacturing plastic tanks for water and liquid storage. The raw materials used in the manufacture are the HR 486 grade of Low Linear Density Polyethylene (LLDPE) polymer as well as H359 polymer supplied by Rotoflo and SASOL Polymers. The roto-moulding manufactured tanks from these polymers are expected to be physically strong and the potable water stored in such tanks has no adverse effects on humans or animals when consumed. The tanks are available in different liquid capacities and different colours up to 10 000 litres.

Makoro Water and Liquid Storage Tanks are manufactured according to customer's requirements. In all cases the temperature of contents should not exceed 60° and must be at ambient pressure. The tanks are designed to withstand the hydrostatic pressure only. These tanks are manufactured from UV resistant virgin material only and no reworked material is used in the manufacturing process. The tanks are lined internally by a black layer of non UV resistant polyethylene.

### MIKROS DUAL STICK-ON LOOP TRAFFIC MONITORING SYSTEM

Mikros Dual Stick-on Loop Traffic Monitoring System consist of a dual stick on loop, RAKTEL X010/20, MICROSAC Card, RAKMAN

Power Manager Card, TELOOP8-100 Loop Card, Battery, Bituthene 5000 or similar tape and GPRS modem to download data (optional).

The dual stick on loops is a temporary loop covered with Bituthene 5000 or similar tape and the loops can only be used once. Generally, the stick-on loops are 3 m x 1 m x 50 mm (nominal dimensions) with one or more turns of cross-linked polyvinylchloride (PVC) wires placed on concrete or asphalts pavements.

Mikros Dual Stick-on Loop Traffic Monitoring Systems are installed over the full width of a roadway on new and existing roads. Site requirements are as specified in Chapter 10 of the TMH3.

### MODULAR FIBRE REINFORCED CONCRETE BUILDING SYSTEM

Modular Fibre Reinforced Concrete Building System is a fibre reinforced concrete structure, with a density of 900 kg/m<sup>3</sup> to 2410 kg/m<sup>3</sup>.

The walls are constructed by erecting pre-oiled temporary shutters taking into account the wall width (100, 150, 180, 220 or 250 mm) and height (2400, 2700 or 3000 mm). The internal face of the walls are further clad with a 40 mm thick EPS insulation sheet and a 6 mm thick fibre cement board.

The light-weight steel re-usable shutters are pre-designed according to architectural design of the structure. The shutters are manufactured to include corner, window and door details.

Foundation and floor slabs are conventional concrete. The floor slab has starter bars (vertical steel reinforcements) at 300 centres, 100 mm deep and 300 mm high for anchoring the wall to the footing. The floor slab must be at least 150 mm above the normal ground level at any point around the building. All steel reinforcement bars (size and spacing) are always the responsibility of a registered competent professional engineer.

The roof is constructed of conventional standard light-weight steel or timber trusses, and clad with metal sheeting, concrete roof tiles or Agrément approved cladding.

### PERMANENT DUAL TRAFFIC MONITORING SYSTEM - TELOOP8

Permanent Dual Traffic Monitoring System with TELOOP8 consist of a dual intrusive loop, RAKTEL X010/20, MICROSAC Card, RAKMAN Power Manager Card, TELOOP8-100 Loop Interface Card, Battery, ZAP3 lightning protection unit, Colseal or similar approved sealant and GPRS modem to download data (optional). The TELOOP8 is an eight channel self-tuning high performance digital loop detector with a lightning protection unit called ZAP3 (powered using 12V).

TELOOP8 loops are permanent embedded loops into concrete or asphalt pavement covered with Colseal or similar approved sealant. Loops are 3 m x 1 m x 50 mm (nominal dimensions) with one or more turns of cross-linked polyvinylchloride (PVC) wires and are installed over the full width of a roadway on new and existing roads and as per client specification. Site requirements are as specified in Chapter 10 of the TMH3.



#### **PERMANENT DUAL TRAFFIC MONITORING SYSTEM - TELOOP8-F**

Permanent Dual Traffic Monitoring System with TEOLOOP8-F consist of a dual intrusive loop, RAKTEL X010/20, MICROSAC card, RAKMAN Power Manager Card, Battery, TEOLOOP8-F-100 Loop interface card, ZAP3 and ZAP4 lightning protection unit, Colseal or similar approved sealant and GPRS modem to download data (optional). The TEOLOOP8-F is an eight channel self-tuning high performance digital loop detector with a lightning protection unit called ZAP3 (powered using 12V) and ZAP4 (powered using TEOLOOP8-F directly to the DB15 ribbon cable header).

TEOLOOP8-F dual intrusive loops are permanent embedded loops into concrete or asphalt pavement covered with Colseal or similar approved sealant. Loops are 3 m x 1 m x 50 mm (nominal dimensions) with one or more turns of cross-linked polyvinylchloride (PVC) wires and are installed over the full width of a roadway on new and existing roads and as per client specification. Site requirements are as specified in Chapter 10 of the TMH3

#### **PERMANENT AXLE TRAFFIC MONITORING SYSTEM - AUTOPIZO8**

Permanent Axle Traffic Monitoring System with AUTOPIZO8 is a combination of dual intrusive loops and piezo sensors. The system consist of a dual intrusive loop, RAKTEL X010/20, MICROSAC card, RAKMAN Power Manager Card, Battery, AUTOPIZO8 axle interface card, Single axle sensor, Colseal or similar approved sealant and GPRS modem to download data. The AUTOPIZO8 axle interface card evaluates the signals from vehicles and automatically scales the threshold and sensitivity levels per individual channel. For the AUTOPIZO8 card to operate effectively a minimum number of light vehicles must traverse the Piezo sensors.

Dual intrusive loops are permanent embedded loops into concrete or asphalt pavement covered with Colseal or similar approved sealant. Loops are 3 m x 1 m x 50 mm (nominal dimensions) with one or more turns of cross-linked polyvinylchloride (PVC) wires and are installed over the full width of a roadway on new and existing roads. The piezo sensors are installed in the same manner as the dual intrusive loop using the RG58 coaxial cable as feeder and are regarded as a single axle sensor. Site requirements are as specified in Chapter 10 of the TMH3.

### PERMANENT AXLE TRAFFIC MONITORING SYSTEM - PICOTEL8

Permanent Axle Traffic Monitoring System with PICOTEL8 consist of a dual intrusive loop, piezo sensors, RAKTEL X010/20, MICROSAC card, RAKMAN Power Manager Card, Battery, PICOTEL8 axle interface card, Single axle sensor, Colseal or similar approved sealant and GPRS modem to download data. Permanent Axle Traffic Monitoring System with PICOTEL8s is a combination of dual intrusive loop and piezo sensors. The PICOTEL8 card is a fully digitally adjustable and does not require any potentiometer adjustments. The PICOTEL8 card allows for diagnostic (graphical) sensor display when using the TelWin program.

Dual intrusive loops are permanent embedded loops into concrete or asphalt pavement covered with Colseal or similar approved sealant. Loops are 3 m x 1 m x 50 mm (nominal dimensions) with one or more turns of cross-linked polyvinylchloride (PVC) wires and are installed over the full width of a roadway on new and existing roads. The Piezo sensors are installed in the same manner as the loop wire using the RG58 coaxial cable as feeders and are regarded as a single axle sensor. Site requirements are as specified in Chapter 10 of the TMH3.

### PERMANENT DUAL TRAFFIC MONITORING SYSTEM - WYPROS I PWIMs

Permanent Axle Traffic Monitoring System with WYPROS I PWIMs consist of a dual intrusive loop, Piezo sensors, RAKTEL X010/20, MICROSAC card, RAKMAN Power Manager Card, Battery, WYPROS I PWIM axle interface card, Single axle sensor, WINTER98 temperature card, Colseal or similar approved sealant and GPRS modem to download data. Permanent Axle Traffic Monitoring System with WYPROS I PWIMs is a combination of dual intrusive loops and piezo sensors. The WYPROS I PWIM card is to process the signals from up to four piezo weigh sensors. WYPROS I PWIM card needs to have a WINTER98 Piezo temperature card to read the temperature of a temperature probe.

Dual intrusive loops are permanent embedded loops into concrete or asphalt pavement covered with Colseal or similar approved sealant. Loops are 3 m x 1 m x 50 mm (nominal dimensions) with one or more turns of cross-linked polyvinylchloride (PVC) wires and are installed over the full width of a roadway on new and existing roads. The Piezo sensors are installed in the same manner as the intrusive loop using the RG58 coaxial cable as feeders and are regarded as a single axle sensor. Site requirements are as specified in Chapter 10 of the TMH3.



### POLYFORM BUILDING SYSTEM

Polyform Building System utilizes factory produced wall panels. The design and approval of the foundation are always the responsibility of approved competent person.

The external wall panel consists of 2800 mm x 250 mm x 105 mm thick expanded polystyrene (EPS) modules with a density of 12 kg/m<sup>3</sup>, forming a central core of 100 mm x 75 mm x 80 mm which is filled with (reinforced) concrete of 25 Mpa. The modules are finished with 15 mm thick plaster both sides. The wall panels have an overall thickness of 135 mm.

Internal walls are 2800 mm x 250 mm x 100 mm with same composition as the external walls with a central cavity of 60 mm x 50 mm x 40 mm.

The roof comprises conventional timber trusses with light- or heavy-weight cladding and insulated with 80 mm thick rigid EPS with density of 15 kg/m<sup>3</sup> in between the trusses, following the slope of the rafters.

Window and door frames are fixed on site into openings after the erection of the wall panels.

Plumbing and electrical conduits should be pre-fixed or surface mounted onto the wall panels.

### PRO CLOSE SLIP-CLUTCH GARDEN BIB TAPS

Pro Close Slip-clutch Garden Bib Taps are 15 mm in diameter, Class 2 (in terms of **SANS 1021**) screw down and manufactured from polyacetal resin.

The taps are intended for use for potable water shut off and garden hose pipe connection in all areas of South Africa.

This certificate and Agrément South Africa's assessment apply only to Pro Close slip-clutch taps that are manufactured by Kielder Komponente cc as described and illustrated in this certificate, and where the terms and conditions of certification are complied with.

### PRO-PHALT INFRARED ROAD REPAIR SYSTEM

The Pro-Phalt Infrared Road Repair System is used to repair bituminous surfaces on pavements damaged by potholes and trench crossings.

Repairs are affected by:

- heating the damaged area of the bituminous surface using an infrared heater to between 180 and 200°C
- reworking/recycling the existing surface layer material with new binder and asphaltic material (to make up any shortfall in material) over the damaged area
- raking the surface to tie in with existing surface levels and then compacting.

### SELCRETE BUILDING SYSTEM

Selcrete™ Building System comprises a mixture of Expanded Polystyrene (EPS) beads, cement and solution of water with liquid binding agent to form hollow blocks. The blocks have a compressive strength of 7 Mpa and a dry density of between 250 kg/m<sup>3</sup> to 600 kg/m<sup>3</sup>. These blocks are produced in moulds on site or factory with sizes of 590 x 190 x 150 mm and 590 x 190 x 190 mm for internal and external walls respectively. The holes are 80 mm diameter.

The blocks are laid in conventional bonding method with mortar mixed with Sikalite® (powdered waterproofing admixture for mortar) as a binding agent. A 20 mm tremnet Polyvinyl Chloride (PVC) mesh is applied to the external walls and finished off with plaster on both sides and painted accordingly.

Foundations are conventional and are always the responsibility of an approved competent person. Roof is of light-weight steel or timber trusses with metal sheeting or concrete tiles or Agrément South Africa approved cladding.

All services are conventional and electrical conduits and plumbing pipes are either surface mounted or grouted in to the walls. These services must be installed in accordance with good building practice.



### SHOUGUANG PREFABRICATED BUILDING SYSTEM

Shouguang Prefabricated Building System is a single storey structure that utilises factory produced wall and roof panels.

The design and approval of the foundation are always the responsibility of a registered professional competent engineer. The steel frames conforms to the requirement of **SANS 517** and are generally 2800 mm high and 600 mm wide and manufactured from 78 mm x 1.2 mm thick hot-dip galvanised steel that conforms to the requirement of **SANS ISO 4998**, **SANS 121/ISO 1461** and **SANS ISO 3575**.

The external and internal wall panels are 2800 mm x 600 mm x 90 mm thick with tongue and groove steel edges consisting of 6 mm fibre cement boards on both sides encapsulating foam cement with a density of 517 kg/m<sup>3</sup>. The roof structures are constructed from medium gauge galvanised steel trusses that are designed and erected in accordance with **SANS 517** and are the responsibility of a professional registered competent engineer. Trusses are clad with roof panels made of 70 mm thick fibre cement board encapsulating foam cement with light- or medium-weight roof cladding on top.

The panels are delivered on site with factory-fitted window and door frames (steel, aluminium or Agrément approved) and are purposely made to suit the design of the building system.

Plumbing and electrical conduits can be pre-fixed or surface mounted onto the composite panels.

### STERLING BUILDING SYSTEM

The Sterling Building System is for single-storey structures. Foundations are the conventional cast in-situ concrete surface beds with thickened edge beams. They are always the responsibility of a professional registered competent engineer.

External wall panels are 158 mm thick and comprise two skins of 6 mm Fibre cement boards which are separated by 100 mm x 100 mm plastic spacers creating a 100 mm thick cavity. The cavity is filled with lightweight reinforced concrete. The internal face of the panel is further clad with a 40 mm thick EPS insulation sheet and a 6 mm thick Fibre cement board.

The internal wall panels are 112 mm thick and similar to external wall panels but are without the 40 mm thick EPS insulation.

The roof structure consists of timber or steel trusses with heavy- or light-weight cladding. A professional registered competent engineer must always design the roof to provide support to the gable wall as well as any additional bracing between trusses as required.

All other services are conventional.



### SUTHERLAND SHEEN COATING SYSTEM

The Sutherland Sheen Coating System is an interior and exterior two-coat application waterproofing acrylic emulsion paint for use in all regions of South Africa for all types of occupancy classifications (**SANS 10400: Table 1 of Regulations A (20) (1)**), on sound, suitably prepared, external and internal substrates as follows:

- sand-cement plaster
- sand-cement bagged finishes
- cast in-situ concrete/precast concrete
- the above surfaces previously painted with PVA paint and
- prepared gypsum and fibre cement boards.

### SUTHERLAND TEX COATING SYSTEM

The Sutherland Tex Coating System is an exterior two-coat waterproofing marble coating system for use in all regions of South Africa for all types of occupancy classifications (**SANS 10400: Table 1 of Regulations A (20) (1)**), on sound, suitably prepared, external and internal substrates as follows:

- sand-cement plaster
- sand-cement bagged finishes
- cast in-situ concrete/precast concrete
- surfaces with unsightly hairline cracks
- the above surfaces previously painted with PVA paint and
- prepared gypsum and fibre cement boards.



## TCE PLASTIC WATER STORAGE TANKS

TCE Plastic Water Storage Tanks are manufactured through rotational moulding process. This method is well known and is a suitable and reliable method of manufacturing water storage tanks. The raw materials used in the manufacture are the HR 486 grade of Low Linear Density Polyethylene (LLDPE) polymer as well as the H359 polymer supplied by SASOL. The physical and chemical properties are specified in the SASOL Polymer data sheet.

Rotomoulding manufactured tanks from these polymers are expected to be physically strong and the water stored in such tanks when consumed has no adverse effects on humans or animals. The tanks are available in different liquid capacities, shapes and different colours and 2500 litres being the largest.

## TENSA FINGER RSFD BRIDGE DECK JOINT

Tensa Finger RSFD Bridge Deck Joint is a steel cantilever finger expansion joint suitable for light and heavy traffic loading, with movement range between 60 mm and 500 mm. It features noise reducing surfacing, due to the sinusoidal geometry of the interlocking fingers.

The certificate covers the use of Tensa Finger RSFD Bridge Deck Joint in all areas of South Africa. The joint is manufactured by mageba in Switzerland. It was assessed as being suitable for use in concrete bridge structures. Tensa Finger RSFD Bridge Deck Joint is suitable for use on bridge deck joints where:

- the maximum movement range is as follows:
  - o 60 mm – 500 mm
- the reinforcement steel is installed at a spacing of 200 mm
- the ends of the finger elements are cut at an angle of 15° with a recess of 5mm
- the maximum vertical movement is 5 mm in order to maintain good rigid quality
- joints can be delivered prepared for connection to either asphalt or concrete
- where the transversal slope is 0%, the drainage channel uses a 1.5% slope (design of the EPDM channel)
- the traffic volume is either 60 km/h, 100km/h or 130 km/h
- the finger plates are stressed into position and the bolt holes are filled with high strength epoxy resin
- the cover plates are screwed at the edge profile of the deck side and slid onto the provided space of the edge profile on the abutment side
- the drainage channel is cleaned out as per the suggested construction method (once a year in urban environments)



### TES STICK-ON LOOP TRAFFIC MONITORING SYSTEM

TES Non-Intrusive Loop Traffic Monitoring System consist of a dual stick on loop, PADVARK traffic logger, Battery, Bituthene 3000 tape and GSM modem to download data (optional).

The dual stick on loops is a temporary loop covered with Bituthene 3000 or similar tape and the loops can only be used once. Generally, the stick-on loops are 2.3 m x 1 m x 50 mm (nominal dimensions) with twin flex polyvinylchloride (PVC) wires placed on concrete or asphalts pavements.

TES Non-Intrusive Loop Traffic Monitoring Systems are installed over the full width of a roadway on new and existing roads. Site requirements are as specified in Chapter 10 of the **TMH3**.

### UL-M 20/10 THIN BITUMINOUS ROAD SURFACING SYSTEM

UL-M 20/10 is a thin bituminous road surfacing system generally laid to a nominal compacted thickness ranging from 20- 40 mm. Principally it consists of a blend of modified bituminous binder Evatech U (EVA), graded crushed stone (aggregates) of nominal size 10 mm and a filler. The UL-M 20/10 is applied by a paver over a tack coat. It is designed to improve skid resistance and where required, reduce permeability.

UL-M 20/10 was developed in the 1980's in France by Enterprise Jean Lefebvre and it carries the British Board of Agrément certification (Roads and Bridges Agrément Certificate No 01/H047). It is extensively used around the world including Europe, USA, and South America. It has successfully been used on a number of roads in South Africa. National Asphalt (Pty) Ltd is licensed to manufacture and install the product in South Africa.

The mix design, manufacturing and application of the product is strictly controlled and under the supervision of an approved competent person and approved by the manufacturer's Technical Manager. The mix proportions may vary slightly from project to project, depending on the traffic, substrate (road base) and the actual properties of the stone received. Aggregates must meet the standard specifications for road works with respect to grading, strength, shape, polished stone value and aggregate/bitumen compatibility etc.







# CERTIFICATES GRANTED



ABACUS EZEESPACE BUILDING SYSTEM



BESTA BOARD BUILDING SYSTEM




BOEN ECOSOLUTIONS BUILDING SYSTEM




BRAVOMAX BUILDING SYSTEM





DIRECT SANITATION APPLICATION SYSTEM



DURAFOIL DSD REFLECTIVE ROOF INSULATION FOIL




ECOBOND NON-TRADITIONAL SOIL STABILIZER



EVERITE SIPOREX AAC BUILDING SYSTEM




GEO PANEL FORMWORK SYSTEM



GEOPLAST MODULO FOUNDATION SYSTEM






ITAS ACCESS CONTROL DOORS



I-WALL BUILDING SYSTEM




JETS VACUUM SANITATION SYSTEM



KWIKSPACE MODULAR BUILDING SYSTEM



MAKORO WATER AND LIQUID STORAGE TANKS



MIKROS DUAL STICK-ON LOOP TMS





PERMANENT DUAL TMS - TELOOP8




PERMANENT DUAL TMS - TELOOP8-F



PERMANENT AXLE TMS - AUTOPIZO8



PERMANENT AXLE TMS - PICOTEL8



PERMANENT DUAL TMS - WYPROS | PWIMs




MODULAR FIBRE REINFORCED CONCRETE BUILDING SYSTEM





POLYFORM BUILDING SYSTEM



PRO CLOSE SLIP-CLUTCH GARDEN BIB TAPS



PRO-PHALT INFRARED ROAD REPAIR SYSTEM



SELCRETE BUILDING SYSTEM



SHOUGUANG PREFABRICATED BUILDING SYSTEM



STERLING BUILDING SYSTEM






SUTHERLAND SHEEN COATING SYSTEM



SUTHERLAND TEX COATING SYSTEM



TCE PLASTIC WATER STORAGE TANKS



TENSA FINGER RSFD BRIDGE DECK JOINT



TES STICK-ON-LOOP TMS



UL-M 20/10 THIN BITUMINOUS ROAD SURFACING SYSTEM





## DIRECTORY OF ACTIVE CERTIFICATES



## Bridge Deck Joints

Thormajoint Bridge Deck Expansion Joint System (DS)  
Thormajoint Bridge Deck Expansion Joint System  
Maurer D80C (FP) Bridge Deck Expansion Joint  
Maurer Multi-Element Bridge Deck Expansion Joint  
BSP 80 Bridge Deck Expansion Joint  
Honel E80 Bridge Deck Expansion Joint  
Honel GAM 80-480 Series Bridge Deck Expansion Joint  
Febajoint Bridge Deck Expansion Joint  
Britflex (BEJ) Bridge Deck Expansion Joint System  
Tensa Finger RSFD Bridge Deck Joint

## Certificate Holder

DSC-Zendon cc  
Bridge Jointing & Rehabilitation Contractors  
DSC-Zendon cc  
DSC-Zendon cc  
DSC-Zendon cc  
Honel Structural Products (Pty) Ltd  
Honel Structural Products (Pty) Ltd  
StonCor Africa (Pty) Ltd  
StonCor Africa (Pty) Ltd  
Bridge Jointing & Rehabilitation Contractors

## Ceilings

Isoboard® Nail Up Insulated Ceilings

Isofoam South Africa (Pty) Ltd

## Damp-proofing

Gundle USB 170 GB Under Surface Bed Membrane  
Gundle Gunplas DPC 250  
Gundle USB 170 GB Damp-proof Membrane  
Gundle Anti-termite Damp-proof Course and Membrane

Gundle API (Pty) Ltd  
Gundle API (Pty) Ltd  
Gundle API (Pty) Ltd  
Novara Profile Extrusions (Pty) Ltd t/a Gundle API

## Insulation

Isoboard® Cavity Wall Insulation  
Isoboard® Inverted Roof Insulation  
Isoboard® Over Purlin Roof Insulation  
Isotherm Thermal Insulation  
Isoboard® Over Rafter and Truss Insulation

Isofoam South Africa (Pty) Ltd  
Isofoam South Africa (Pty) Ltd  
Isofoam South Africa (Pty) Ltd  
Brits Textiles, division of Seardel (Pty) Ltd  
Isofoam South Africa (Pty) Ltd

## Plumbing

Contactim  
Geberit HDPE Above Ground Soil  
Geberit Pluvia Syphonic Roof Drainage System

Contactim (Pty) Ltd  
Geberit Southern Africa (Pty) Ltd  
Geberit Southern Africa (Pty) Ltd

## Product

Calcamite Water and Liquid Storage Tanks  
EcoTanks Water and Liquid Storage Tanks

Calcamite Sanitary Services (Pty) Ltd  
Ecopolymers cc t/a EcoTanks

## Products

Rototank™ Water and Liquid Storage Tanks  
Yebo Water and Liquid Storage Tanks  
KRM Water and Liquid Storage Tanks  
High Density Polymer Envirodoor  
TCE Plastic Water Storage Tanks  
Makoro Water and Liquid Storage Tanks

## Certificate Holder

Affirm Manufacturing Services (Pty) Ltd  
Quick Traders 1029cc  
KRM Plastics (Pty) Ltd  
Envirosan Sanitation Solutions cc  
Tariosync (Pty) Ltd t/a TCE Plastics  
Makoro Tank Technologies (Pty) Ltd

## Roofing products

Gundle Gunplas UT 180 Undertile Membrane  
Gundle Gunplas UT 250 Undertile Membrane  
Monier Roofing Undertile Membrane  
Gundle UT Woven Tile Underlay  
Marulelo Roofing Undertile Membrane  
Compactroll Ridge and Hip Capping  
Easyflash  
Spunsulation 3 Roofing Radiant Barrier  
Spunsulation 5 Roofing Radiant Barrier  
Spunsulation 5 Light Roofing Radiant Barrier  
Spunsulation Roofing Undertile Membrane  
Spunsulation 4 Contractors Choice  
Spunsulation Illumina Roofing Radiant Barrier

Gundle API (Pty) Ltd  
Gundle API (Pty) Ltd  
Monier Roofing (Pty) Ltd SA  
Gundle API (Pty) Ltd  
Monier Roofing (Pty) Ltd SA  
Monier Roofing (Pty) Ltd SA  
Monier Roofing (Pty) Ltd SA  
Spunbond Holdings (Pty) Ltd t/a Spunchem Interna  
Spunbond Holdings (Pty) Ltd t/a Spunchem Interna  
Spunbond Holdings (Pty) Ltd t/a Spunchem Interna  
Spunbond Holdings (Pty) Ltd t/a Spunchem Interna  
Spunbond Holdings (Pty) Ltd t/a Spunchem Interna  
Spunbond Holdings (Pty) Ltd t/a Spunchem Interna

## Sanitation Products

Calcamite 1250 litre On-site Sanitary Disposal System  
Calcamite 1500 litre Liquid Capacity On-site System  
Cemforce Easy Loo VIP Toilet System  
Cemforce Easy Loo Urine Diversion Toilet System  
SMARTSAN Recycle Digester Sanitation System  
Ventilated Improved Pit and Urine Diversion Toilet System  
Jets Vacuum Sanitation System  
Direct Sanitation Application System

Calcamite Sanitary Services (Pty) Ltd  
Calcamite Sanitary Services (Pty) Ltd  
Cemforce cc  
Cemforce cc  
Nano Water Technologies Africa (Pty) Ltd  
Envirosan Sanitation Solutions cc  
SA Biotech (Pty) Ltd  
Sanitas Advanced Technology Sanitation (Pty) Ltd

## Thin Bituminous Surfacing Systems

NOVACHIP Thin Bituminous Surfacing System  
UL-M 20/10 Thin Bituminous Road Surfacing  
AquaFRICTION Course Road Surfacing System  
FrictionPave: Thin Bituminous Surfacing System

Murray and Roberts Infrastructure (Pty) Ltd  
National Asphalt (Pty) Ltd  
Aqua Transport and Plant Hire (Pty) Ltd  
FrictionPave Partnership JV





### Wall Coatings

Cemcrete Cemwash  
Cemcrete Stipplecrete  
Techfin System  
Glutone Wall Coating  
Khusela Emanzini Coating System  
Top Paint Waterrepellent Latex Paint  
Prominent Paints Waterproofing Wall Coating  
Weatherprufe Sealcoat Coating System  
Sheerflex Coating System  
Valamanzi Coating System  
Optiflash Waterproofing System  
Plascon Wallseal Coating System  
Nucover Wall Coating  
Sutherland Sheen Coating System  
Sutherland Tex Coating System  
Amoriguard Wall Coating System

### Walling and Building Systems

Cavcon Modular Building System  
National and Overseas Factory Built Buildings  
Goldflex 800 Building System  
Goldflex 100 Building System  
FSM Building System  
Neopor Building System  
Hydraform Building System  
Robust Building System  
Aruba™ 2000 Series Building System  
Goldflex 800 Seismic Building System  
Ikhaya Future House Building System  
Cemforce GRC Building System  
Ikhaya Future House Double- and Multi-Storey Building System  
Banbric Building System  
ITAS Modular Building System  
Alternative Steel Frame Building System  
Bright-Kid Container Conversions  
Blast Building System  
Mi Panel 1 Building System  
Mega Building System

### Certificate Holder

Cemcrete (Pty) Ltd  
Cemcrete (Pty) Ltd  
Technical Finishes (Pty) Ltd  
Technical Finishes (Pty) Ltd  
Ultraline (Pty) Ltd  
Top Paints (Pty) Ltd  
Prominent Paints (Pty) Ltd  
Market Demand Trading No 263 (Pty) Ltd  
Dekro Paints (Pty) Ltd  
Optima Coatings (Pty) Ltd  
Optima Coatings (Pty) Ltd  
Kansai Plascon (Pty) Ltd  
Xeracote cc t/a Olympia International Paints  
O'Grady Coatings (Pty) Ltd  
O'Grady Coatings (Pty) Ltd  
Amoriguard (Pty) Ltd

Cavcon Building Systems  
National and Overseas Modular Construction  
Group Five Construction (Pty) Ltd  
Group Five Construction (Pty) Ltd  
Fabricated Steel Manufacturing Co (Pty) Ltd  
Khuthala Consulting (Pty) Ltd  
Hydraform Developments (Pty) Ltd  
Robust Structures (Pty) Ltd  
Robust Structures (Pty) Ltd  
Group Five Construction (Pty) Ltd  
Ikhaya Futurehouse Systems (Pty) Ltd  
Cemforce cc  
Ikhaya Futurehouse Systems (Pty) Ltd

Banbric Building cc  
I.T.A Security Co (Pty) Ltd  
Tower Technology (Pty) Ltd.  
Breidert Education Development cc  
Didutex (Pty) Ltd  
MiBT SA Pty (Ltd)  
Mega Green Structures (Pty) Ltd

## Walling and Building Systems continued

Compressed Earth Blocks Building System  
Concretex Building System  
Harmili Building System  
UCO Solidwall Building System  
Oceansafe Building System  
Tutungeni Building Systems  
Khaya Readykit Building System  
Cellular Concrete Building System  
RBM Greenbuild Building System  
Uvuyo Building System  
Adventure Shells PVC Building System  
RPM PHD Building System  
Specialised Insulated Panel Building System  
UkuZwana Building System  
Power Profile Building System  
Ezee Build Modular Building System  
GHS Wall Technology Building System  
RIC Prefabricated Building System  
Sterling Building System  
JK Structure Building System  
Benex Masonry Building System  
FSM FR Polycore Building System  
Green Crete Building System  
Besta Board Building System  
Boen EcoSolutions Building System  
GeoPanel Formwork System  
Geoplast Modulo Foundation System  
Shouguang Prefabricated Building System  
Kwikspace Modular Building System  
Abacus Ezeespace Building System  
Abod House Building System  
Selcrete Building System  
Everite Hebel AAC Building System  
Besa Building System  
Besa 2 Building System  
Bravomax Building System

## Certificate Holder

Use-It  
Paveprint cc T/A Concretex  
Kwikspace Modular Buildings (Pty) Ltd  
United Fibre Cement Company (Pty) Ltd  
Exelis Development (Pty) Ltd  
Tutungeni Precast cc  
Khaya Readykit (Pty) Ltd  
NRF housing (Pty) Ltd  
RBM Greenbuild (Pty) Ltd  
Uvuyo Trading 109 (Pty) Ltd  
Adventure Shells (Pty) Ltd  
Pego Phd (Pty) Ltd  
Specialised Panel Manufacturing cc  
UkuZwana Project Management Solutions (Pty) Ltd  
Shell Case (Pty) Ltd  
Ezee Build Developments cc  
GHS GMBH  
Rodger Ian Carter's Technical Services (Pty) Ltd  
Sanjo FabTech Sterling (Pty) Ltd  
GIB Developments (Pty) Ltd  
Garden Cities NPC (RF)  
Fabricated Steel Manufacturing Co (Pty) Ltd  
Get Connected Holdings (Pty) Ltd  
Fast Track Contracting Africa (Pty) Ltd  
EcoSolutions (Pty) Ltd  
GeoPlast South Africa (Pty) Ltd  
GeoPlast South Africa (Pty) Ltd  
Shouguang Sunrise Construction Engineering Co., Ltd  
Kwikspace Modular Buildings (Pty) Ltd  
Waco Africa (Pty) Ltd t/a Abacus Space Solutions  
HMR Homes (Pty) Ltd  
Hjott South Africa (Pty) Ltd  
Everite (Pty) Ltd  
Agrément South Africa  
Agrément South Africa  
Bravomax (Pty) Ltd

## Waterproofing

Derbigum SP Waterproofing

Derbigum Manufacturing (Pty) Ltd



### Waterproofing continued

Index Fidia 'P' Roof Waterproofing  
Index Testudo 20 Waterproofing

### Certificate Holder

ABE Construction Chemicals (Pty) Ltd  
ABE Construction Chemicals (Pty) Ltd

### Software

BSIMAC (Version 9)  
DesignBuilder (Version 4.0)  
DesignBuilder (Version 3.1)  
StarFront Software  
IES Virtual Environment Software (Version VE 2013)  
Crealco U-Solve Whole Window and Door

Alec Johannsen Consulting Engineers  
Greenbuild Consultants  
Greenbuild Consultants  
Wispeco (Pty) Ltd  
Integrated Environmental Solutions(IES) LTD.  
Wispeco (Pty) Ltd

### Roads Products

Enviro Prime  
Pro-Phalt Infrared Road Repair System  
Non-tacky Tack Coat (nt-cote)

Tarspray cc  
Pro-Phalt SA (Pty) Ltd  
Tarspray cc

### Traffic Monitoring Systems

Mikros Dual Stick-on Loop Traffic Monitoring System  
Permanent Dual Traffic Monitoring System with TELOOP8  
Permanent Dual Traffic Monitoring System with  
TELOOP8-F  
Permanent Axle Traffic Monitoring System with  
AUTOPIZO8  
Permanent Axle Traffic Monitoring System with PICOTEL8  
Permanent Axle Traffic Monitoring System with WYPROS I  
PWIM  
TES Non-Intrusive Loop Traffic Monitoring System

Mikros Systems (Pty) Ltd t/a Syntell Group Company  
Mikros Systems (Pty) Ltd t/a Syntell Group Company  
Mikros Systems (Pty) Ltd t/a Syntell Group Company  
  
Mikros Systems (Pty) Ltd t/a Syntell Group Company  
  
Mikros Systems (Pty) Ltd t/a Syntell Group Company  
Mikros Systems (Pty) Ltd t/a Syntell Group Company  
  
TES Trust



## DIRECTORY OF INACTIVE CERTIFICATES



### Bathroom and Toilet Units

Rocla Bathroom & Toilet Units

### Certificate Holder

Rocla (Pty) Ltd

### Insulation

Exterior Insulation Facade System

Guy Bright (Pty) Ltd

### Products

Betcrete Polycrrete Window Sill

MG Innovation t/a Betcrete

Betcrete Polymer Window and Door Frames

MG Innovation t/a Betcrete

### Roofing Products

Infra-Flash Self Adhesive Sealant

Infrasat A Business Unit of Aveng Africa Limited

Cyclo Roof Tiles

Cyclocor (Pty) Ltd

Nam-TeX

Nampak L & CP

Resintile Roof Tiles

Plastiworld Trading (PTY) LTD T/A Resintile

Roofproof 400 Non Woven Undertile Membrane

Astrapak Kwazulu-Natal (Pty) Ltd

Spunsalation 5 Roofing Radiant Barrier

asd

Spunsalation Roofing Radiant Barrier

asd

### Wall Coatings

Brickseal Cementitious Wall Coating

Zambezi Mining Services (Pty) Ltd

Flexiwall Coating System

Duram (Pty) Ltd

PlasterMax

GigaCrete Inc.

### Walling and Building Systems

1DR Build Building System

H W Visser Designing & Planning

CSIR Modular House Building System

CSIR Built Environment

Amsa's Alternative Building System

Arcelor Mittal South Africa Steel Service Centre

Mi Panel 2 Building System

MiBT SA Pty (Ltd)

Amsa's Protea Building System

Arcelor Mittal South Africa Steel Service Centre

Legna Solidwall Building System

Legna Creative Enterprises cc

Cavcon Modular Building System

Cavcon Building Systems

Abkin's J1 Building System (M)

Abkin's Housing System (Pty) Ltd

Abkin's Norman 2 Building System

Abkin's Housing System (Pty) Ltd

Abkin's Simon 4 Building System

Abkin's Housing System (Pty) Ltd

Automapolyblock Building System

Automa Building Products (Pty) Ltd

## Walling and Building Systems continued

CMA Building Foundation Beams  
 Con-Cottage Building System  
 Crane Building System  
 Dri-Block Building System  
 Eapro A Building Method  
 Eapro M Building Method  
 Eco-Construction Building System  
 Estra Building System  
 Formington Phoenix System I  
 Formington Phoenix System II  
 Frame-Tech Building System  
 Gethal Building System  
 House-In-A-Can Building System  
 Innovida Building System  
 Izoblok Building System  
 Joseph Shoshany Chopsa  
 K M L Pre-Engineered Homes  
 Locktite Block Building System  
 LSF Building System  
 LTA Rimon  
 M2 Emmedue Building System  
 Masonite Hardboard Dry-Fill Building System  
 Matla Housing System  
 MDA Housing System  
 Megacom Housing System  
 Megacom Mantag Building System  
 MG SIP Building System  
 Micro-concrete Cladding Building System  
 Modular Home Building System  
 Panelcast Buildings  
 Portable Container Building System  
 RBM Greenbuild Building System  
 Riftec Kit House  
 Sandwich Modular Panel Housing System  
 ScipsT Building System  
 Space Frame Construction System  
 Tronco Building System  
 Vela Steel Building System  
 Vertibar Building System  
 Waffle-Crete Mantag System

## Certificate Holder

Concrete Manufacturers Association  
 CONCOR Holdings (Pty) Ltd  
 Agrément South Africa  
 Dri-Block (Pty) Ltd  
 Eassec (Pty) Ltd  
 Eassec (Pty) Ltd  
 MR Gregory Francis Xavier Walker  
 Estra Homes (SA) (Pty) Ltd  
 Formington Systems (Pty) Ltd  
 Formington Systems (Pty) Ltd  
 Circle Capital Developments (Pty) Ltd  
 Ceiling Solutions (Pty) Ltd  
 HIAC Group of Companies  
 Yokoyo Investments (Pty) Ltd  
 Meeting of Minds cc  
 Stauch Vorster Architects  
 Styrox Holdings (Pty) Ltd  
 Guy Bright (Pty) Ltd  
 Liege Developments & Projects (Pty) Ltd  
 Joseph Shoshany Horizon Homes  
 Thatch Lock cc  
 Use-It  
 Rocla (Pty) Ltd  
 Michael Dyson Associates Ltd  
 Megacom Housing (Pty) Ltd  
 Megacom Housing (Pty) Ltd  
 Marble Gold 231 Pty (Ltd)  
 Anton Bonacich cc  
 Ekhaya Jabulani Housing Projects cc  
 Alan Serritslev  
 Creative Aluminium t/a Merakeng Solutions  
 RBM Greenbuild (Pty) Ltd  
 Tarspray cc  
 University of Pretoria  
 Africa SCIPS cc  
 Isofoam (South Africa) (Pty) Ltd  
 Quick Sill cc  
 Vela Steel Building System (Pty) Ltd  
 Kwenya ya Sebele Trading Enterprise cc  
 United Fibre Cement Company (Pty) Ltd







### Walling and Building Systems continued

Wigwam  
Wolfbrick Building System  
Wonder Panel Building System  
World Housing Solutions Building System  
Yangshu Sandwich Wall Panel Building System  
Zenzele Building System

### Certificate Holder

Freyssinet Posten (Pty) Ltd  
Kwena ya Sebele Trading Enterprise cc  
Kwena ya Sebele Trading Enterprise cc  
Yokoyo Investments (Pty) Ltd  
Yangshu Integrated House Building  
Provincial Administration: Eastern Cape

### Cold Stores

Isowall System

Isowall Southern Africa (Pty) Ltd

### Non-traditional Road Stabilisers

PC For Roads Non-traditional Soil Additive

Marble Gold 453 (Pty) Ltd t/a PowerCem So

# TECHNICAL AGENCY







## This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.



## CONNECT WITH US

### PHYSICAL ADDRESS

Building 2A, CSIR, Meiring Naudé Road, Brummeria, Pretoria

### POSTAL ADDRESS

PO Box 395, Pretoria, 0001, South Africa

### GPS COORDINATES GATE 3 (A FRAME)

S25 44.874 E028 16.523

T +27 12 841 3708

E [agreement@csir.co.za](mailto:agreement@csir.co.za)

Website: [www.agreement.co.za](http://www.agreement.co.za)

ISBN: **978-0-7988-5629-4**